Honeywell

51-52-16U-73 Issue 16 Page 1 of 2

Series APT4000 Transmitter

Model Selection Guide

(pH, Toridal and Contacting Conductivity)

Instructions

APT4000 Transmitter Offers:

- Power Requirements Universal, 20 to 253V AC/DC 45 to 65 Hz
- Standard NEMA 4X, IP65
- Standard Approvals:

General Purpose; also FM Class I, Div 2, Groups A-D

- Standard All models CE Compliant
- High/Low Alarm Relays
- Three mounting types: (must be ordered separately)

Panel Mount Kit
Pipe/Wall Mount Kit

Protective Hood (requires Pipe/Wall Mount Kit)



Instructions

•	Make one selection from Tables using the column below the proper arrow.
	A dot (*) denotes unrestricted availability.

Key Number		ı
<u></u>	-	$\Gamma_{}$

KEY NUMBER	Selection	<u>Availabili</u> t		ity	
Description of Measurement Type					
pH/ORP	APT 4000 PH	\downarrow			
Glass Electrodes: Internal pre-amp used					
Durafet II Electrodes: Cap adapter is required					
Toroidal (Electrodeless) Conductivity	APT 4000 TC		↓		
Contacting Conductivity	APT 4000 CC			\forall	

TABLE I - Optional Equipment

User's Manual	English	E	•	•	•
Future		_ 0 _	٠	•	•
Future		0	٠	•	•

APT4000 Transmitter

Accessories

Accessory Parts Part Number

Mounting Kits (ordered separately from Transmitter)	
Panel Mounting Kit	51205990-001
Pipe/Wall Mounting Kit	51205988-001
Protective Hood (requires pipe/wall kit)	51205989-001
Instruction Manual - pH	70-82-25-103
Instruction Manual - Toroidal (Electrodeless) Conductivity	70-82-25-105
Instruction Manual - Contacting Conductivity	70-82-25-104